380 VOLT



IDROLAVA
Practical and unique

IDROLAVA

TECHNICAL SPECIFICATIONS

The IDROLAVA mobile washing system is a handy technology installed on stainless steel chassis, equipped with pressurization motors and special filters for water treatment, motor with high pressure pump, Cleaning technology and electrical panel with push button and remote control for program activation.

ADVANTAGES

Time saving:
half the washing time.

Practical use

The washing operation takes place in just two phases activated by a **remote control panel on the machine** or by a practical **remote control** that avoids tedious movements for the operator, for immediate and convenient applications.
A Delivery of a chemical solution with very fast rinsing, which to the high cleaning and breaking power of the dirt combines protective properties of the treated surfaces.
B Rinse with water that does not require drying due to its chemical-physical properties, for surfaces free of halons and limescale residues, with an ultra-light effect.

The **production kit** allows the use of the machine in the only functions of **production and supply of osmotized water**, for **filling single-piece tanks**, **wiper trays**, **toilet tanks on board** and for **cleaning of interiors and interior glass**.



COMPONENTS







1. PRE-FILTRATION
Inlet water treatment system with safety micrometric pre-filtration.

2.PRECISE DILUTIONS
Special systems for precise, constant dilutions and fast adjustments.

3. BUTTON/REMOTE CONTROL
Operations are activated by button panel or remote control, for quick and convenient washing. For activation of washing programs and the optional function of producing osmotic water only for other uses.

4.OSMOTIC TREATMENT
Pressurization and vessel electropumps with membranes to produce water with specific physical characteristics, flow rates and pressures.

5.HIGH PRESSURE
High pressure guaranteed by reliable, low-maintenance seramic piston pumps.

6.INOX ROLLER
Sturdy roller with stand for convenient storage of up to 20 mt of hose.

Modelli	Models	BT200
Pressione di lavoro	Working pressure	180 bar - 18 Mpa
Pressione massima	Maximum pressure	200 bar - 20 Mpa
Portata	Flow rate	750 lt/h
Potenza assorbita	Absorbe d power	6 Kw
Fasi/Volt/Hz	Phoses/ Volt/Hz	3 / 380V / 50 HZ
Peso	Weight	160 Kg
Dimensioni cm	Dimensions cm	85x68x130h

Dotazione di serie | Standard equipement

1 Kit di produzione | Production kit
1 Pistola Automatica | Automatic gun
1 Lancia acciaio inox 170cm | Stainless steel pressure washer 170cm height
1 Ugello washjet | Washjet noozle
20 Mt di tubo alta pressione da 1/4" | high pressure tube of 1/4"
2 Telecomandi | Remots
1 Arrotolatore manuale | Manual reel

DETERGENTS AND ADDITIVES

BR1
10 Kg

Special osmotic pre-treatment additive.



M110
10 Kg

Innovative, safe, biodegradable and self-polishing detergent.



FILTER MICROMETRIC

5MCR



CONTACT

Registered office and production
Via Enrico De Nicola, 17
85050 Tito (Pz) - Italia
Tel. +0971 62 90 65
Mob. +39 342 57 08 134

www.buggy114.com
info@buggy114.com

